High-Performance Embedded Systems-on-a-Chip

Sanjay Rajopadhye
Computer Science, Colorado State University

Lecture 5: Guibas-Kung-Thompson Array

IRISA

Outline

- Projects Administrivia
- Manipulating Polyhedra & SRE's
- Optimal Parenthesization Array [GKT 79]

IRISA

Projects already “taken”

- Monica Chawathe & Charllie Ross: Interface generation
- Gautam Gupta: Scheduling/Serializing Reductions
- Dae-Kyoo Kim & Eunjee Song Optimal Prenthesization (protein folding)
- Howard Porter & Stacey Secatch Custom caches
- Lakshmi Renganarayana: Non-systolic SRE’s
- Jian-Pin Yang & Jhongjun Yang SOR Kernels

IRISA

Manipulating Polyhedra and SRE's

Recap: Parameterized Polyhedra:

$$\{z \in \mathcal{Z}^n \mid Qz \geq q\}$$

Dual (alternative, equivalent) representation (vertices/rays):

$$\{z \in \mathcal{Z}^n \mid z = a^T V + b^T R;\ a_i, b_i \geq 0; \sum_i a_i = 1\}$$

Both are useful.

Standard (self-dual) algorithm to transform one to the other.

IRISA

Preimage by (any) affine function

$$
\begin{aligned}
\mathcal{A}(z) &\equiv \mathcal{Z}^n \rightarrow \mathcal{Z}^m \ : \ z \mapsto Az + a \\
\mathcal{P} &\equiv \text{polyhedron} \subseteq \mathcal{Z}^m \\
\mathcal{A}^{-1}(\mathcal{P}) &\equiv \text{PreImage}(\mathcal{P}, \mathcal{A}) \\
&\equiv \{z \in \mathcal{Z}^n \mid \mathcal{A}(z) \in \mathcal{P}\}
\end{aligned}
$$

IRISA

Preimage by (any) affine function

$$
\begin{aligned}
\mathcal{A}(z) &\equiv \mathcal{Z}^n \to \mathcal{Z}^m \ : \ z \mapsto Az + a \\
\mathcal{P} &\equiv \text{polyhedron} \subseteq \mathcal{Z}^m \\
\mathcal{A}^{-1}(\mathcal{P}) &\equiv \text{PreImage}(\mathcal{P}, \mathcal{A}) \\
&\equiv \{z \in \mathcal{Z}^n \mid \mathcal{A}(z) \in \mathcal{P}\} \\
\text{by definition} &= \{z \in \mathcal{Z}^n \mid Az + a \in \mathcal{P}\}
\end{aligned}
$$

IRISA

Preimage by (any) affine function

$$
\begin{aligned}
\mathcal{A}(z) &\equiv \mathcal{Z}^n \to \mathcal{Z}^m \ : \ z \mapsto Az + a \\
\mathcal{P} &\equiv \text{polyhedron} \subseteq \mathcal{Z}^m \\
\mathcal{A}^{-1}(\mathcal{P}) &\equiv \text{PreImage}(\mathcal{P}, \mathcal{A}) \\
&\equiv \{z \in \mathcal{Z}^n \mid \mathcal{A}(z) \in \mathcal{P}\} \\
\text{by definition} &= \{z \in \mathcal{Z}^n \mid Az + a \in \mathcal{P}\} \\
\text{constraint repr.} &= \{z \in \mathcal{Z}^n \mid Q(Az + a) \geq q\}
\end{aligned}
$$

IRISA

Preimage by (any) affine function

$$
\begin{aligned}
\mathcal{A}(z) &\equiv \mathcal{Z}^n \to \mathcal{Z}^m \ : \ z \mapsto Az + a \\
\mathcal{P} &\equiv \text{polyhedron} \subseteq \mathcal{Z}^m \\
\mathcal{A}^{-1}(\mathcal{P}) &\equiv \text{PreImage}(\mathcal{P}, \mathcal{A}) \\
&\equiv \{z \in \mathcal{Z}^n \mid \mathcal{A}(z) \in \mathcal{P}\} \\
\text{by definition} \quad &= \{z \in \mathcal{Z}^n \mid Az + a \in \mathcal{P}\} \\
\text{constraint repr.} \quad &= \{z \in \mathcal{Z}^n \mid Q(Az + a) \geq q\} \\
&= \{z \in \mathcal{Z}^n \mid QAz \geq q - Qa\}
\end{aligned}
$$

IRISA

Preimage by (any) affine function

$$
\begin{aligned}
\mathcal{A}(z) &\equiv \mathcal{Z}^n \to \mathcal{Z}^m \ : \ z \mapsto Az + a \\
\mathcal{P} &\equiv \text{polyhedron} \subseteq \mathcal{Z}^m \\
\mathcal{A}^{-1}(\mathcal{P}) &\equiv \text{PreImage}(\mathcal{P}, \mathcal{A}) \\
&\equiv \{z \in \mathcal{Z}^n \mid \mathcal{A}(z) \in \mathcal{P}\} \\
\text{by definition} \quad &= \{z \in \mathcal{Z}^n \mid Az + a \in \mathcal{P}\} \\
\text{constraint repr.} \quad &= \{z \in \mathcal{Z}^n \mid Q(Az + a) \geq q\} \\
&= \{z \in \mathcal{Z}^n \mid QAz \geq q - Qa\}
\end{aligned}
$$

Result is a polyhedron with constraints $\langle QA, q - Qa \rangle$

IRISA

Image by (unimodular) affine function

$$
\begin{aligned}
\mathcal{A}(z) &\equiv \mathcal{Z}^n \rightarrow \mathcal{Z}^n \ : \ z \mapsto Az + a \\
\mathcal{P} &\equiv \text{polyhedron} \subseteq \mathcal{Z}^n \\
\mathcal{A}(\mathcal{P}) &\equiv \text{Image}(\mathcal{P}, \mathcal{A}) \\
&\equiv \{\mathcal{A}(z) \in \mathcal{Z}^n \mid z \in \mathcal{P}\}
\end{aligned}
$$

IRISA

Image by (unimodular) affine function

$$
\begin{aligned}
\mathcal{A}(z) &\equiv \mathcal{Z}^n \rightarrow \mathcal{Z}^n \ : \ z \mapsto Az + a \\
\mathcal{P} &\equiv \text{polyhedron} \subseteq \mathcal{Z}^n \\
\mathcal{A}(\mathcal{P}) &\equiv \text{Image}(\mathcal{P}, \mathcal{A}) \\
&\equiv \{\mathcal{A}(z) \in \mathcal{Z}^n \mid z \in \mathcal{P}\}
\end{aligned}
$$

Result is a polyhedron with vertices $\langle AV + a \rangle$ and rays $\langle AR + a \rangle$

IRISA

Image by (unimodular) affine function

$$
\begin{aligned}
\mathcal{A}(z) &\equiv \mathcal{Z}^n \rightarrow \mathcal{Z}^n \ : \ z \mapsto Az + a \\
\mathcal{P} &\equiv \text{polyhedron} \subseteq \mathcal{Z}^n \\
\mathcal{A}(\mathcal{P}) &\equiv \text{Image}(\mathcal{P}, \mathcal{A}) \\
&\equiv \{\mathcal{A}(z) \in \mathcal{Z}^n \mid z \in \mathcal{P}\}
\end{aligned}
$$

Result is a polyhedron with vertices $\langle AV + a \rangle$ and rays $\langle AR + a \rangle$

Practical hint: it is also ***preimage*** by $\mathcal{A}^{-1}$

IRISA

Recap: Change of Basis

To obtain an equivalent SRE on applying a *CoB transformation* by $\mathcal{T}$ to a variable X of an SRE:

$$X(z) \quad = \quad \left\{ \begin{array}{ccc} & & \vdots \\ D_i^X & : & g_i(\ldots Y(f(z))\ldots) \\ & & \vdots \end{array} \right.$$

IRISA

Transformation Rules

- Replace each D_i^X by $\mathcal{T}(D_i^X)$, its image by $\mathcal{T}$.
- In the occurrences of a variable on the rhs of the equation for X, replace the dependency f by $f \circ \mathcal{T}^{-1}$, the composition[a] of f and $\mathcal{T}^{-1}$.
- In all occurrences of the variable X on the rhs of *any* equation, replace the dependency f by $\mathcal{T} \circ f$.

---

[a]Note: function composition is rt associative: $(g \circ h)(z) = g(h(z))$.

IRISA

Optimal Parenthesization Array

Compute $C[1, n+1]$, where, for $1 \leq i < j \leq n+1$

$$C[i,j] = \begin{cases} i+1 = j \ : \ f'(i,j) \\ i+1 < j \ : \ \min\limits_{i<k<j} (C[i,k] + C[k,j] + f(i,j,k)) \end{cases}$$

IRISA

Optimal Parenthesization Array

Compute $C[1, n+1]$, where, for $1 \leq i < j \leq n+1$

$$C[i,j] = \begin{cases} i+1 = j \ : \ f'(i,j) \\ i+1 < j \ : \ \min\limits_{i<k<j} (C[i,k] + C[k,j] + f(i,j,k)) \end{cases}$$

Alternatively (à la Cormen et al) compute $C[1, n]$,

where, for $1 \leq i \leq j \leq n$,

$$C[i,j] = \begin{cases} i = j \ : \ 0 \\ i < j \ : \ \min\limits_{i \leq k<j} (C[i,k] + C[k+1,j] + f(i,j,k)) \end{cases}$$

Exercise

Prove that the two are equivalent (hint: substitute for the $i = j + 1$ case in the second one and “simplify”).

IRISA

Exercise

Prove that the two are equivalent (hint: substitute for the $i = j + 1$ case in the second one and “simplify”).

Actual equation (in GKT): $f(i, j, k)$ is *independent of* k:

IRISA

Exercise

Prove that the two are equivalent (hint: substitute for the $i = j + 1$ case in the second one and “simplify”).

Actual equation (in GKT): $f(i, j, k)$ is *independent of* k:

compute $C[1, n + 1]$, where, for $1 \leq i < j \leq n + 1$

$$C[i, j] = w_{i,j} + \min_{i<k<j} (C[i, k] + C[k, j])$$

Observations/Questions

- Total volume of computation: $\approx \frac{1}{6}n^3$
- Total I/O volume : $\approx \frac{1}{2}n^2$ (actually n^2)
- Triangular array: PE $[i, j]$ computes $C[i, j]$

IRISA

Observations/Questions

- Total volume of computation: $\approx \frac{1}{6}n^3$
- Total I/O volume : $\approx \frac{1}{2}n^2$ (actually n^2)
- Triangular array: PE $[i, j]$ computes $C[i, j]$
- What values are used to compute a given $C[i, j]$?

IRISA

Observations/Questions

- Total volume of computation: $\approx \frac{1}{6}n^3$
- Total I/O volume : $\approx \frac{1}{2}n^2$ (actually n^2)
- Triangular array: PE $[i, j]$ computes $C[i, j]$
- What values are used to compute a given $C[i, j]$?
- Where is a given $C[i, j]$ used?

IRISA

Observations/Questions

- Total volume of computation: $\approx \frac{1}{6}n^3$
- Total I/O volume : $\approx \frac{1}{2}n^2$ (actually n^2)
- Triangular array: PE $[i, j]$ computes $C[i, j]$
- What values are used to compute a given $C[i, j]$?
- Where is a given $C[i, j]$ used?
- With whom is a given $C[i, j]$ “combined”?

IRISA

Observations/Questions

- Total volume of computation: $\approx \frac{1}{6}n^3$
- Total I/O volume : $\approx \frac{1}{2}n^2$ (actually n^2)
- Triangular array: PE $[i, j]$ computes $C[i, j]$
- What values are used to compute a given $C[i, j]$?
- Where is a given $C[i, j]$ used?
- With whom is a given $C[i, j]$ “combined”?
- Where is it combined?

IRISA

Observations/Questions

- Total volume of computation: $\approx \frac{1}{6}n^3$
- Total I/O volume : $\approx \frac{1}{2}n^2$ (actually n^2)
- Triangular array: PE $[i, j]$ computes $C[i, j]$
- What values are used to compute a given $C[i, j]$?
- Where is a given $C[i, j]$ used?
- With whom is a given $C[i, j]$ “combined”?
- Where is it combined?

How the array works

- $C[i, j]$ is computed at time $2(j - i)$

How the array works

- $C[i, j]$ is computed at time $2(j - i)$
- It is then sent horizontally and vertically, travelling at a rate of one PE per cycle for exactly $j - i$ more cycles.

IRISA

How the array works

- $C[i, j]$ is computed at time $2(j - i)$
- It is then sent horizontally and vertically, travelling at a rate of one PE per cycle for exactly $j - i$ more cycles.
- Afterwards, it travels at a slower rate of one PE every *two* cycles.